

ANYCERT-SAA-AS/NZS 5000.2-450/750V-SDI

Single core PVC Wire



应用

- Suitable for switch gear and control panel wiring. It is also used for other fixed wiring in protected duct slots, such as construction and the installation of movable houses and caravans.

结构

- Conductor, Class 1, Class 2 or Class 5 copper wire
- according to AS/NZS1125
- Insulated to AS/NZS 3808, PVC V90

特点

- Environmentally protect materials, no harmful
- substances, in compliance with RoHS or REACH directives

性能

- Operating voltage: 450/750V
- Minimum bending radius:
Mobile installation: 15x cable OD
Fixed installation: 4x cable OD
- Operating temperature range:
Mobile installation: -5° C to +90° C
Fixed installation: -40° C to +90° C
- Flame retardant and flame retardant: IEC 60332.1

Type	Core*size	O.D.	Weight
5000.2SDI	1×1.0	2.5	13.9
5000.2SDI	1×1.5	2.8	19.2
5000.2SDI	1×2.5	3.4	30.6
5000.2SDI	1×4	4.2	47.6
5000.2SDI	1×6	4.7	67.1
5000.2SDI	1×10	6.0	111.0
5000.2SDI	1×16	7.1	169.2

Customized cable acceptable.