

ANYCERT-UL/CUL-IRRIGATION CABLE

UL1551 Irrigation Cable/Sprinkle system Cable



应用

- Suitable for central control system of field and underground irrigation system, automatic sprinkler system, underground sprinkler system.
- UL83standard
- The multi-standard cable UL-CSA and comply with US and
- Canadian standards, enabling the cable to be used in the North American market at the same time

结构

- Single bare copper wire conductor
- Special PE mixed core wire insulation (color can be customized according to customer requirements)
- PVC mixture outer sheath (color can be customized according to customer requirements)
- Rated temperature: 75°C
- Working voltage: 30V

页码

Item	AWG	Cores	Insulation Material	Insulation Thickness mm	Insulation O. D mm	Jacket Material	Jacket Thickness mm	Jacket O.D mm
1001IRRI1C10	10	1	HDPE	0.45	3.5	Special PVC	0.85	5.2
1001IRRI1C12	12	1	HDPE	0.45	2.95	Special PVC	0.8	4.55
1001IRRI1C14	14	1	HDPE	0.45	2.53	Special PVC	0.8	4.13
1001IRRI1C16	16	1	HDPE	0.45	2.19	Special PVC	0.7	3.59
1001IRRI1C18	18	1	HDPE	0.41	1.84	Special PVC	0.65	3.14
1001IRRI2C18	18	2	HDPE	0.41	1.84	Special PVC	0.66	5.0
1001IRRI3C18	18	3	HDPE	0.41	1.84	Special PVC	0.67	5.31
1001IRRI4C18	18	4	HDPE	0.41	1.84	Special PVC	0.68	5.81
1001IRRI5C18	18	5	HDPE	0.41	1.84	Special PVC	0.72	6.41
1001IRRI6C18	18	6	HDPE	0.41	1.84	Special PVC	0.72	6.54
1001IRRI7C18	18	7	HDPE	0.41	1.84	Special PVC	0.74	7.0
1001IRRI8C18	18	8	HDPE	0.41	1.84	Special PVC	0.74	7.4
1001IRRI9C18	18	9	HDPE	0.41	1.84	Special PVC	0.74	7.77
1001IRRI10C18	18	10	HDPE	0.41	1.84	Special PVC	0.74	8.12

*Can provide customers with special order

If you have special requirements for core wire, outer sheath, operating temperature range, etc., please consult