

ANYCERT-SAA-AS/NZS 60245.4-450/750V

H07RN-F Rubber Cable



应用

- Suitable for heavy equipment such as: engines, large tools, motors, agricultural machinery, wind power or construction equipment. It is also suitable for direct laying in machines, such as elevators and cranes, wind power towers, etc. They can be used for protective and fixed installations in pipes and equipment, as well as for connecting cables such as motors.

特点

- Flame retardant, UV resistant, ozone resistant
- SAA-compliant cable for use in Australia, New Zealand.

结构

- Conductor in accordance with IEC60228-5, soft
- copper wire or tinned copper wire
- Conforms to VDE0207 Rubber EI4 insulation, EPR
Compliant with VDE0282 Rubber EM3 Sheath, PCP

Operating voltage: 450/750V

性能

- Minimum bending radius:
- Mobile installation: 15x cable OD
Fixed installation: 4x cable OD
- Operating temperature range:
Mobile installation: -5° C to +90° C
Fixed installation: -40° C to +90° C
- Flame retardant and flame retardant: IEC 60332.1

Type	Cores*size	O.D.	Type	Cores*size	O.D.	Type	Cores*size	O.D.
60245H07RNF	1×1.0	7	60245H07RNF	3×4	16.2	60245H07RNF	5×16	33.3
60245H07RNF	2×1.0	8	60245H07RNF	4×4	17.9	60245H07RNF	1×25	15.8
60245H07RNF	3×1.0	11.5	60245H07RNF	5×4	19.9	60245H07RNF	2×25	30.7
60245H07RNF	4×1.0	12.5	60245H07RNF	1×6	8.3	60245H07RNF	3×25	33.0
60245H07RNF	5×1.0	13.5	60245H07RNF	2×6	16.8	60245H07RNF	4×25	36.6
60245H07RNF	1×1.5	7.1	60245H07RNF	3×6	18.0	60245H07RNF	5×25	40.4
60245H07RNF	2×1.5	11.0	60245H07RNF	4×6	20.0	60245H07RNF	1×35	17.9
60245H07RNF	3×1.5	11.9	60245H07RNF	5×6	22.2	60245H07RNF	2×35	35.5
60245H07RNF	4×1.5	13.1	60245H07RNF	1×10	10	60245H07RNF	3×35	37.1
60245H07RNF	5×1.5	15	60245H07RNF	2×10	24	60245H07RNF	4×35	42
60245H07RNF	1×2.5	6.6	60245H07RNF	3×10	25.5	60245H07RNF	5×35	45
60245H07RNF	2×2.5	13.5	60245H07RNF	4×10	28	60245H07RNF	1×50	21
60245H07RNF	3×2.5	14.5	60245H07RNF	5×10	30.5	60245H07RNF	2×50	41
60245H07RNF	4×2.5	15.5	60245H07RNF	1×16	10.7	60245H07RNF	3×50	44
60245H07RNF	5×2.5	17	60245H07RNF	2×16	27.5	60245H07RNF	4×50	48.5
60245H07RNF	1×4	7.5	60245H07RNF	3×16	29.5	60245H07RNF	5×50	52
60245H07RNF	2×4	15	60245H07RNF	4×16	32			