

ANYCERT-BS-624Y

BS6004 624Y PVC Flat Cable



应用

- Suitable for fixed installation in dry or wet locations, or for laying in trunks or pipes.

结构

- Conductor according to EN 60228, Class 1 or 2
 - PVC insulation
 - PVC outer sheath
- (Insulation sheath color can be customized according to customer's requirements)

页码

特点

- Environmentally protect materials, in accordance with the ROHS Directive
- cables with CE and other approvals meet European standards, enabling cables to be adapted to different European market needs

性能

- Operating voltage: 300/500V
- Operating temperature: -5° C to +70° C
- Flame retardant and flame retardant: IEC 60332-1-2

Item	mm ²	Conductor type	O.D. mm	Thickness mm	Insulation O.D.mm	Earth wire section size SQ.mm	O. D. mm	Standard O.D. mm	KG/100M
1004624Y001	1	1	1.13	0.7	2.6	1.0	2.6x6.4	4.4x8.0	75
1004624Y0015	1.5	1	1.38	0.7	2.8	1.0	2.8x6.8	4.6x8.4	85
1004624Y0025	2.5	1	1.78	0.7	3.2	1.5	3.2x8.1	5.2x9.9	120
1004624Y004	4	2	2.55	0.7	4.0	1.5	4.0x9.7	6.0x11.5	170
1004624Y006	6	2	3.12	0.7	4.5	2.5	4.5x11.5	6.5x13.5	230
1004624Y0010	10	2	4.05	0.7	6.1	4.0	5.2x14.8	7.2x14.2	390
1004624Y0013	16	2	5.10	0.7	7.1	6.0	5.7x15.4	8.1x15.9	575

*customized cable acceptable