

# ANYCERT-UL/CUL/CSA-UL2464

## UL2464 Multi core communication cable ( shield optional )



### 应用

- This product is used for the connection of UL series rated voltage below 300 / 300V, electrical and electronic, instrumentation, machinery and electronic equipment, signal devices inside household appliances or computer signals inside buildings, the product has certain heat resistance, conductors can Working at 80 °C, it can work at 60 °C in the environment exposed to oil and other solvents. The wire has strong anti-interference ability, especially suitable for computer signal connection.

- Rated temperature: 80 °C
- Working voltage: 300V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

### 结构

- Stranded of fine bare copper wire conductor or tinned copper wire
- PVC or SRPVC mixed core wire insulation (color can be customized according to customer requirements)
- Stranded composite cable
  - \* Insulated plastic film coating or special PVC mixture inner sheath
- \* Aluminum foil Mylar 100% coated shield
- \* (Tinned) copper wire shield braid, coverage rate up to 85%
- PVC mixture outer sheath (color can be customized according to customer requirements)
- Hit \* for optional structure

页码

Item	conductor			No	Insulation		Jacket		Maximum conductor Resistance	Minimum insulation resistance	Voltage resistant
	size	wires/ mm	O.D.		thick	O.D.	thick	O.D.			
	AWG	No./mm	mm		mm	mm	mm	mm			
10012464003028	28	7/0.127	0.38	3	0.23	0.88	0.80	3.70	223.75	10	1500
10012464004028				4				3.90			
10012464005028				5				4.20			
10012464006028				6				4.50			
10012464007028				7				4.50			
10012464008028				8				4.80			
10012464009028				9				5.10			
10012464010028				10				5.30			
10012464011028				11				5.40			
10012464012028				12				5.40			
10012464013028				13				5.70			
10012464014028				14				5.70			
10012464015028				15				5.90			
10012464025028				25				7.60			
10012464037028				37				8.30			
10012464050028				50				9.60			