

# ANYCERT-UL/CUL-UL 1061

## UL 1061 PVC Electric wire



### 应用

- This product is used for the connection of UL series rated voltage below 300V, electrical and electronic, instrumentation, machinery and electronic equipment, home appliances power and signal devices or building interior.
- Use standard thickness, easy to peel and cut With anti-acid, oil, moisture, mildew, environmental protection and other characteristics
- The multi-standard wiring cable UL-CSA and other approvals comply with US and Canadian standards, enabling the cable to be used in the North American market at the same time.

### 结构

- Single or multiple strands of finely stranded bundles of 30-14AWG bare copper wire or tinned copper wire
- Semi-rigid PVC insulation (color can be customized according to customer requirements)
- Rated temperature: 80 °C
- Working voltage: 300V
- Oil resistance, flame retardant : CSA FT1 and UL VW-1

页码

Item	Conductor type	Conductor			Insulation		Maximum conductor Resistance 20°C	Minimum insulation resistance	voltage
		size	Wire number	Wire O.D.	Thickness	O.D.			
		AWG	No./mm	mm	mm	mm	Ω/km	MΩ.Km	V
1001106130S7	Stranded conductor	30	7/0.10	0.30	0.23	0.80	354.24	15	2000
1001106128S7		28	7/0.127	0.38	0.23	0.88	223.75		
1001106126S7		26	7/0.16	0.48	0.23	0.98	139.73		
1001106124S11		24	11/0.16	0.61	0.23	1.11	93.3		
1001106122S17		22	17/0.16	0.76	0.23	1.26	55.0		
1001106120S26		20	26/0.16	0.94	0.23	1.54	34.6		
1001106118S41		18	41/0.16	1.49	0.23	1.84	21.8		
1001106116S26		16	26/0.254	1.88	0.23	2.20	13.7		
1001106114S41		14	41/0.254	0.32	0.23	2.50	8.62		
10011061028		Solid conductor	28	1/0.32	0.404	0.23	0.82		
10011061026	26		1/0.404	0.511	0.23	0.90	142.79		
10011061024	24		1/0.511	0.643	0.23	1.01	89.39		
10011061022	22		1/0.643	0.813	0.23	1.14	54.3		
10011061020	20		1/0.813	1.024	0.23	1.41	33.9		
10011061018	18		1/1.024	1.31	0.23	1.68	21.4		
10011061016	16		1/1.31	1.64	0.23	1.99	13.5		
10011061014	14		1/1.64	0.30	0.23	2.3	8.45		

\*customized cable acceptable