

ANYCERT-BS-6491B

BS7211 6491B LSZH Electric Wire



应用

- Suitable for installation in dry or humid indoor environments, for wiring in lighting fixtures and in valuable property equipment that must be protected against damage by fire. Can connect lights, equipment, switch gear, distribution boxes, etc.

结构

- Conductor according to EN 60228, Class 1 or 2
- LSZH (Low Smoke and Halogen Free) Insulation (Insulation colors can be customized upon request)

特点

- No toxic gases are produced during combustion, in accordance with EN 60754
- In case of fire, low smoke density in accordance with EN61034
- Environmentally protect materials, in accordance with the ROHS Directive

性能

- Operating voltage: 450/750V
- Operating temperature: -5° C to +90° C
- Flame retardant and flame retardant: IEC 60332-1-2

Item	Section size	Insulate thickness	Jacket O.D.	KG/100M
10046491B001	1	0.7	2.6	14
10046491B0015	1.5	0.7	2.8	20
10046491B0025	2.5	0.8	3.7	34
10046491B004	4	0.8	4.2	51
10046491B006	6	0.8	4.8	71
10046491B010	10	1.0	6.1	120
10046491B016	16	1.0	7.1	180
10046491B025	25	1.2	8.9	285
10046491B035	35	1.2	10.1	380
10046491B050	50	1.4	11.8	510
10046491B070	70	1.4	13.6	715
10046491B095	95	1.6	15.9	990
10046491B120	120	1.6	17.5	1230
10046491B150	150	1.8	19.4	1510
10046491B185	185	2.0	21.7	1900
10046491B240	240	2.2	24.5	2490
10046491B300	300	2.4	27.5	3050
10046491B400	400	2.6	30.9	3900
10046491B500	500	2.8	34.5	4880
10046491B630	630	2.8	38.4	6210

*Customized cable acceptable