

ANYCERT-UL/CUL/CSA-UL 10330

UL 10330 PUR Electric wire



应用

- Suitable for internal wiring of general electronic and electrical equipment.
 - Soft use standard thickness, easy to peel and cut
 - With anti-acid, oil, moisture, mildew, environmental protection and other characteristics
- Using environmentally protect materials, with ROHS.
The multi-standard cable UL-CSA and other approvals comply with US and Canadian standards.

结构

- Single or multiple strands of finely stranded bare copper wire and tinned copper wire
- Wear-resistant and oil-resistant polyurethane PUR mixture insulation (color can be customized according to customer requirements)
- Rated temperature: 90 °C
- Working voltage: 600V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

页码

Item	type	conductor			insulation		Maximum conductor Resistance	Minimum insulation resistance	Voltage resistant
		size	wires/mm	O.D.	thick	O.D.			
		AWG	No./mm	mm	mm	mm	Ω/km	MΩ.Km	V
100110239030	strand ed	30	7/0.10	0.30	0.76	1.82	354.24	15	3000
100110239028		28	7/0.127	0.38	0.76	1.9	223.75		
100110239026		26	7/0.16	0.48	0.76	2.0	139.73		
100110239024		24	11/0.16	0.61	0.76	2.13	93.3		
100110239022		22	17/0.16	0.76	0.76	2.28	55.0		
100110239020		20	26/0.16	0.94	0.76	2.47	34.6		
100110239018		18	41/0.16	1.49	0.76	2.7	21.8		
100110239016		16	26/0.254	1.88	0.76	3.01	13.7		
100110239014		14	41/0.254	2.37	0.76	3.4	8.62		
100110239012		12	65/0.254	3.40	0.76	3.89	5.43		
100110239010		10	105/0.254	0.25	0.76	4.92	3.41		
100110239030S1	solid	30	1/0.254	0.32	0.76	1.77	354.24	15	3000
100110239028S1		28	1/0.32	0.404	0.76	1.84	223.75		
100110239026S1		26	1/0.404	0.511	0.76	1.92	139.73		
100110239024S1		24	1/0.511	0.643	0.76	2.03	93.3		
100110239022S1		22	1/0.643	0.813	0.76	2.16	55.0		
100110239020S1		20	1/0.813	1.02	0.76	2.33	34.6		
100110239018S1		18	1/1.02	1.29	0.76	2.54	21.8		
100110239016S1		16	1/1.29	0.30	0.76	2.81	13.7		