

# ANYCERT-UL-SPT

## UL SPT-1 SPT-2 Power cord



### 应用

- Used in household clocks, fans, radios and other electrical products.
- UL62 standard
- Use standard thickness, easy to peel and cut
- Has the characteristics of oil resistance, moisture resistance, mildew resistance, environmental protection, ROHS.
- UL-CSA comply with US and Canadian standards, enabling the cable to be used in the North American market at the same time

### 结构

- Strands of fine bare copper wire conductors
- Special PVC mixed core insulation (color can be customized according to customer requirements)
- The core wires are separated and arranged in parallel
- Rated temperature: 105 °C
- Working voltage: 300V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

页码

Item	type	conductor			Core	insulation		20°C Resistant	Insulation Resistant
		size	wire	OD		thickness	O.D.		
		AWG	No./mm	mm	No	mm	mm	Ω/km	MΩ.Km
1001SPT1002018	SPT-1	18	41/0.16	1.18	2	0.76	2.70x5.40	21.8	15
1001SPT1003018	SPT-2	18	41/0.16	1.18	3	0.76	2.70x8.10	21.8	
1001SPT1002020		20	26/0.16	0.94	2	0.76	2.5x5.0	34.6	
1001SPT1003020		20	26/0.16	0.94	3	0.76	2.5x7.5	34.6	

