

# ANYAPPS-ELEVATORCABLE-6491,6491B,2 491,2491B

## BS7211Standard LSZH elevator cable



### 应用



This is a halogen-free single-core wire, suited to be installed in dry or wet indoor environments for wiring of lighting fixtures and wiring in the fire protection to prevent damage to valuable property and equipment must be carried out. Especially used in densely populated or valuable equipment of buildings, such as airports, ships, subway, and public or private transport such as trams, trains, and elevators.

### 结构

Solid or multi-strand fine bare copper wires twist as conductor, in class 1,2 or 5  
Insulation:LSZH material comply with DIN VDE 0282 (color can be customized according to customer requirements)

### 特点

Does not release toxic and corrosive substances ,and does not release hydrogen chloride, to avoid such hazards. Chemical resistance, particularly oil, small bend radius, flame retardant, resistant to ozone, low smoke when burned no toxic substances, the maximum guarantee of life.

### 性能

Rated voltage: 450/750V

Minimum bend radius: 5x cable diameter

Operating temperature range: -5 ° C to +90 ° C

Anti-radiation intensity: up to  $20 \times 10^6$  cJ/kg

Part No.	size sqmm	Insulated Thicknes s mm	Appr. O.D. mm	Weigth Kg/km
200LSZH6491001	1	0.7	2.6	14
200LSZH64910015	1.5	0.7	2.8	20
200LSZH64910015A	1.5	0.7	3.0	21
200LSZH64910025	2.5	0.8	3.4	33
200LSZH64910025A	2.5	0.8	3.7	34
200LSZH6491004	4	0.8	4.2	51
200LSZH6491006	6	0.8	4.8	71
200LSZH6491010	10	1.0	6.1	120
200LSZH6491016	16	1.0	7.1	180
200LSZH6491025	25	1.2	8.9	285
200LSZH6491035	35	1.2	10.1	380
200LSZH6491050	50	1.4	11.8	510
200LSZH6491070	70	1.4	13.6	715
200LSZH6491095	95	1.6	15.9	990
200LSZH64910120	120	1.6	17.5	1230
200LSZH64910150	150	1.8	19.4	1510
200LSZH64910185	185	2.0	21.7	1900
200LSZH64910240	240	2.2	24.5	2490
200LSZH64910300	300	2.4	27.5	3050
200LSZH64910400	400	2.6	30.9	3900
200LSZH64910500	500	2.8	34.5	4880
200LSZH64910630	630	2.8	38.4	6210