

ANYCERT-CE/TUV/VDE-H05VV5-F

H05VV5-F Oil resistant PVC Control Cable



应用

- Suitable for daily applications such as home environment, kitchen, office, etc., and can also be used in humid conditions.
- Small outer diameter to save space for cable installation
- Meet strict electrical and mechanical performance requirements
- Firm and soft, with excellent resistance to grease and chemicals. Using environmentally protect materials, in line with ROHS directive
- CE / TUV and other approvals comply with European standards.

结构

- Compliant with VDE0295. IEC60228 fine stranded (tinned) copper wire
- Meet VDE 0281.HD 21.5 & IEC 60227 special flame retardant PVC insulation, PVC jacket.
- Working voltage: 300V / 500V
- Minimum bending radius:
Mobile installation: 15x cable outer diameter
Fixed installation: 4x cable outer diameter
- Operating temperature range:
Mobile installation: -5 °C to + 70 °C
Fixed installation: -40 °C to + 70 °C
- Oil resistance, flame retardant:
IEC 60332.1 / HD 405.2 and VDE0207-4

Item	(nxmm ²)	thickness (mm)	Cable OD (mm)		Weight Km (kg)
			max	min	
1002H05VV5F0020005	2x0.5	0.6	5.6	7.2	53
1002H05VV5F00200075	2x0.75	0.6	6.0	7.6	63
1002H05VV5F002001	2x1.0	0.6	6.4	8.0	71
1002H05VV5F0020015	2x1.5	0.7	7.4	9.0	90
1002H05VV5F0020025	2x2.5	0.8	8.9	11.0	132
1002H05VV5F002004	2x4.0	0.8	10.0	12.0	177
1002H05VV5F0030005	3x0.5	0.6	5.9	7.7	56
1002H05VV5F00300075	3x0.75	0.6	6.4	8.0	67
1002H05VV5F003001	3x1.0	0.6	6.8	8.4	77
1002H05VV5F0030015	3x1.5	0.7	8.0	9.8	122
1002H05VV5F0030025	3x2.5	0.8	9.6	12.0	180
1002H05VV5F003004	3x4.0	0.8	11.0	13.0	241
1002H05VV5F0040005	4x0.5	0.6	6.4	8.4	72
1002H05VV5F00400075	4x0.75	0.6	6.8	8.6	88
1002H05VV5F004001	4x1.0	0.6	7.6	9.4	101
1002H05VV5F0040015	4x1.5	0.7	9.0	11.0	131
1002H05VV5F0040025	4x2.5	0.8	10.5	13.0	197
1002H05VV5F004004	4x4.0	0.8	12.0	14.0	266