

# ANYCERT-SAA-AS/NZS 5000.3-450/750V-CRP

## 多芯聚氯乙烯圆屏蔽/铠装电缆



### 应用

- Widely used in power plants, industrial and switch gear installations and power companies, but also in indoor, cable conduit circuit control. Strong resistance to electromagnetic interference, lightning strikes and uniform electric field, improving the quality of power supply.

### 结构

- Conductor, Class 1, Class 2 or Class 5 copper wire
- according to AS/NZS1125
- Insulated to AS/NZS 3808, PVC V90
- Shielded weave (tinned) copper wire with 85% coverage
- Various types of armor shields can also be customized
- Conforms to AS/NZS 3808 standard sheath, PVC 5V-90
- Operating voltage: 450/750V
- Flame retardant: IEC 60332.1

### 特点

- Environmentally protect materials, no harmful substances, in compliance with RoHS or REACH directives
- SAA certified cable for use in Australia, New Zealand.

### 性能

- Minimum bending radius:
- Mobile installation: 15x cable OD
- Fixed installation: 4x cable OD
- Operating temperature range:
- Mobile installation: -5° C to +90° C
- Fixed installation: -40° C to +90° C

Type	Core*size	O.D.	Weight
5000.3CRP	2×0.5	10.4	192.4
5000.3CRP	3×0.5	10.72	208.7
5000.3CRP	4×0.5	11.27	230.6
5000.3CRP	5×0.5	11.87	254.1
5000.3CRP	6×0.5	13.1	295.9
5000.3CRP	7×0.5	13.1	304.3
5000.3CRP	8×0.5	13.73	330
5000.3CRP	9×0.5	14.57	361.8
5000.3CRP	10×0.5	15.2	387.8
5000.3CRP	11×0.5	15.52	405.3
5000.3CRP	12×0.5	15.52	413.7
5000.3CRP	13×0.5	16.07	437.7
5000.3CRP	14×0.5	16.07	446.1
5000.3CRP	15×0.5	16.87	488.5
5000.3CRP	16×0.5	16.87	496.9
5000.3CRP	17×0.5	17.5	524.1

Type	Core*size	O.D.	Weight
5000.3CRP	18×0.5	17.5	532.5
5000.3CRP	19×0.5	17.5	540.9
5000.3CRP	20×0.5	17.82	559.1
5000.3CRP	21×0.5	18.13	576.7
5000.3CRP	22×0.5	18.97	610.6
5000.3CRP	23×0.5	20	655.7
5000.3CRP	24×0.5	20	664.1
5000.3CRP	25×0.5	20.32	682.8
5000.3CRP	26×0.5	20.32	691.2
5000.3CRP	27×0.5	20.32	699.6
5000.3CRP	28×0.5	20.87	725.3
5000.3CRP	29×0.5	20.87	733.8
5000.3CRP	30×0.5	20.87	742.2
5000.3CRP	31×0.5	21.47	769.7
5000.3CRP	32×0.5	21.47	778.1
5000.3CRP	18×0.5	10.8	207.7