

ANYCERT-CE/TUV-H03VV-F/H05VV-F

Multi cores PVC / PVC flex cable



应用

- The European unified standard flexible rope cable is used for electronic and electrical equipment designed for export to Europe, such as office equipment and supplies, and as a replacement for equipment produced in Europe during maintenance, repair and operation.

- Small outer diameter to save space for cable installation
- Meet strict electrical and mechanical performance requirements

Using environmentally protect materials, in line with ROHS directive

Multi-standard wiring cables CE / TUV and other approvals comply with European standard.

结构

- Compliant with VDE0295. IEC60228 stranded (tinned) copper wire
 - Meets VDE 0281. HD 21.5 & IEC 60227 polyvinyl chloride PVC insulation, PVC sheath
- (The color of insulation sheath can be customized according to customer requirements)

- Working voltage: H03VV-F: 300V/300V
H05VV-F: 300V/500V

- Minimum bending radius:
Mobile installation: 15x cable outer diameter

- Fixed installation: 4x cable outer diameter

Operating temperature range:

- Mobile installation: -5 °C to +70 °C

- Fixed installation: -40 °C to +70 °C

Flame retardant: IEC 60332-1-2

Item	(nxmm2)	thickness (mm)	Cable OD (mm)		weight Km (kg)
			max	min	
1002H03VVF0020005	2x0.5	0.6	5.2	6.8	39
1002H03VVF00200075	2x0.75	0.6	5.6	7.2	48
1002H03VVF0030005	3x0.5	0.6	5.6	7.2	48
1002H03VVF00300075	3x0.75	0.6	6.0	7.6	59
1002H05VVF0020005	2x0.5	0.6	5.6	7.2	53
1002H05VVF00200075	2x0.75	0.6	6.0	7.6	63
1002H05VVF0020001	2x1.0	0.6	6.4	8.0	71
1002H05VVF0020015	2x1.5	0.7	7.4	9.0	90
1002H05VVF0020025	2x2.5	0.8	8.9	11.0	132
1002H05VVF002004	2x4.0	0.8	10.0	12.0	177
1002H05VVF0030005	3x0.5	0.6	5.9	7.7	56
1002H05VVF00300075	3x0.75	0.6	6.4	8.0	67
1002H05VVF0030001	3x1.0	0.6	6.8	8.4	77
1002H05VVF0030015	3x1.5	0.7	8.0	9.8	122
1002H05VVF0030025	3x2.5	0.8	9.6	12.0	180