

ANYCERT-BS-624B

BS7211 624B Halogen Free Flat Cable



页码

应用

- Suitable for receptacles and lighting for potentially life-threatening and equipment caused by pyrotechnic emissions and toxic fumes, dry or wet locations, suitable for laying in trunking or ducting.

特点

- No toxic gases are produced during combustion, in accordance with EN 60754
 - In case of fire, low smoke density in accordance with EN61034
 - Environmentally protect materials, in accordance with the ROHS Directive
- cables with CE and other approvals meet European standards, allowing the cables to be adapted to different European market needs.

结构

- Conductor according to EN 60228, Class 1 or 2
- XLPE (cross-linked polyethylene) insulation
- LSZH (Low Smoke and Halogen Free) sheath
(Custom colors are available upon request)

性能

- Operating voltage: 300/500V
 - Operating temperature: -5° C to +70° C
- Flame retardant and flame retardant: IEC 60332-1-2

Item	size	Conductor type	thickness	O.D.	Ground wire section size	Jacket O.D. Min.mm	Jacket O.D. Max.mm	KG/100M
1004624B001	1	1	0.7	2.6	1.0	2.6x6.4	4.4x8.0	75
1004624B0015	1.5	1	0.7	2.8	1.0	2.8x6.8	4.6x8.4	85
1004624B0025	2.5	1	0.8	3.2	1.5	3.2x8.1	5.2x9.9	120
1004624B004	4	2	0.8	4.0	1.5	4.0x9.7	6.0x11.5	170
1004624B006	6	2	0.8	4.5	2.5	4.5x11.5	6.5x13.5	230

*customized cable acceptable.