

ANYCERT-BS-6381B

BS7211 6381B LSZH Single Core Electric Wire



应用

- Suitable for installation in dry or humid indoor environments, for wiring of lighting fixtures and for wiring in valuable property equipment where fire protection is required to prevent damage.

结构

- Conductor according to EN 60228, Class 1 or 2
- XLPE (cross-linked polyethylene) insulation
- LSZH (Low Smoke and Halogen Free) sheath (Custom colors are available upon request)

特点

- No toxic gases are produced during combustion, in accordance with EN 60754
- In case of fire, low smoke density in accordance with EN61034
- Environmentally protect materials, in accordance with the ROHS Directive

性能

- Operating voltage: 300/500V
- Operating temperature: -5° C to +90° C
- Flame retardant and flame retardant: IEC 60332-1-2

Item	mm ²	Thickness mm	Jacket O.D. mm	KG/100M
10046381B025	25	0.9	11.0	315
10046381B035	35	0.9	12.1	420
10046381B050	50	1.78	14.7	535
10046381B070	70	2.14	16.5	787
10046381B095	95	2.52	19	1052
10046381B0120	120	2.03	20.06	1447
10046381B0150	150	2.25	22.7	1649
10046381B0185	185	2.32	25.2	2026
10046381B0240	240	2.25	28.2	2659
10046381B0300	300	2.25	31.4	3253
10046381B0400	400	2.35	34.8	4240
10046381B0500	500	2.36	38.5	5260
10046381B0630	630	2.38	43.4	6600

*customized cable acceptable.