

ANYCERT-BS-6181Y

BS6004 6181Y Double Insulation Electric Wire



应用

- It can be used as a connection cable in machine tools and electrical equipment.

结构

- Conductor according to EN 60228, Class 1 or 2
- PVC insulation
- PVC outer sheath
(Insulation sheath color can be customized according to customer's requirements)

特点

- Environmentally friendly materials, in accordance with the ROHS Directive
- cables with CE and other approvals meet European standards, enabling cables to be adapted to different European market needs.

性能

- Operating voltage: 300/500V
- Operating temperature: -5° C to +70° C
- Flame retardant and flame retardant: IEC 60332-1-2

Item	section	Wire size	1 st thickness	2ed thickness	O.D.	KG/100M
XY10046181XY06	6	0.41	1.2	1.2		
XY10046181XY10	10	0.41	1.2	1.2		
XY10046181XY16	16	0.41	1.2	1.2	13	24
XY10046181XY25	25	0.41	1.4	1.4	15.3	32
XY10046181XY35	35	0.41	1.4	1.4	16.7	38
XY10046181XY50	50	0.41	1.4	1.4	16.8	42
XY10046181XY70	70	0.51	1.4	1.4	18.1	50
XY10046181XY95	95	0.51	1.6	1.6	20	59
XY10046181XY120	120	0.51	1.6	1.6	22.1	71
XY10046181XY150	150	0.51	1.8	1.8	14.8	36.5
XY10046181XY185	185	0.51	2.0	1.8	18.4	45.5
XY10046181XY240	240	0.51	2.2	1.8	19.9	53
XY10046181XY300	300	0.51	2.4	2.0	20	60.5
XY10046181XY400	400	0.51	2.6	2.1	21.6	73
XY10046181XY500	500	0.61	2.8	2.2	25.7	95
XY10046181XY630	630	0.61	2.8	2.4	26.3	109.5

*customized cable acceptable.