

ANYCERT-SAA-AS/NZS 5000.2-450/750V-SRF

Multi cores PVC Cable



应用

- Widely used in power plants, industrial and switchgear installations and power companies, but also indoors, in cable conduits for circuit control.

结构

- Conductor, Class 1, Class 2 or Class 5 copper wire
- according to AS/NZS1125
- Insulated to AS/NZS 3808, PVC V90
- Conforms to AS/NZS 3808 standard sheath, PVC 5V-90

特点

- Environmentally protect materials, no harmful substances, in compliance with RoHS or REACH

性能

- Operating voltage: 450/750V
- Minimum bending radius:
 - Mobile installation: 15x cable OD
- Fixed installation: 4x cable OD
- Operating temperature range:
 - Mobile installation: -5° C to +90° C
 - Fixed installation: -40° C to +90° C
- Flame retardant and flame retardant: IEC 60332.1

Type	Core*size	O.D.	Weight
5000.2SRF	4×1.0	8.9	96.9
5000.2SRF	5×1.0	9.7	115.7
5000.2SRF	4×1.5	9.7	122.8
5000.2SRF	5×1.5	10.5	147.7
5000.2SRF	4×2.5	11.2	178.9
5000.2SRF	5×2.5	12.3	216.9
5000.2SRF	4×4	13.3	261.9
5000.2SRF	5×4	14.6	319.4
5000.2SRF	4×6	14.6	350.1
5000.2SRF	5×6	16	428.8
5000.2SRF	4×10	17.9	553.6
5000.2SRF	5×10	19.8	681.3
5000.2SRF	4×16	20.8	812.7
5000.2SRF	5×16	22.9	1003.5



*Customized cable acceptable.