

ANYCERT-BS-318A

BS6004 318A PVC/PVC Insulated and Jacket Cable



应用

- Designed to withstand harsh external temperatures of -40°C to maintain flexibility. Making them particularly suitable for outdoor applications and for temperatures below zero where flexibility is required.

特点

- Environmentally protect materials, in accordance with the
 - ROHS Directive
- cables with CE and other approvals meet European standards, enabling cables to be adapted to different European market

结构

- Conductor to EN 60228, Class 5
- PVC insulation
- Special cold-resistant PVC sheathing
(Insulation sheath color can be customized according to customer's requirements)

性能

- Operating voltage: 300/500 V
- Operating temperature: -40°C to $+70^{\circ}\text{C}$
- Flame retardant: IEC 60332-1-2

Item	nxmm ²	Thickness mm	Cable O.D. (mm)		Km/kg
			min	max	
10042183Y0020005	2 x 0.5	0.6	5.6	7.2	53
10042183Y00200075	2 x 0.75	0.6	6.0	7.6	63
10042183Y002001	2 x 1.0	0.6	6.4	8.0	71
10042183Y0020015	2 x 1.5	0.7	7.4	9.0	90
10042183Y0020025	2 x 2.5	0.8	8.9	11.0	132
10042183Y002004	2 x 4.0	0.8	10.0	12.0	177
1004318A0030005	3 x 0.5	0.6	5.9	7.7	56
1004318A00300075	3 x 0.75	0.6	6.4	8.0	67
1004318A003001	3x 1.0	0.6	6.8	8.4	77
1004318A0030015	3x 1.5	0.7	8.0	9.8	122
1004318A0030025	3 x 2.5	0.8	9.6	12.0	180
1004318A003004	3 x 4.0	0.8	11.0	13.0	241
1004318A0040005	4 x 0.5	0.6	6.4	8.4	72
1004318A00400075	4 x 0.75	0.6	6.8	8.6	88
1004318A004001	4x 1.0	0.6	7.6	9.4	101
1004318A0040015	4x 1.5	0.7	9.0	11.0	131
1004318A0040025	4 x 2.5	0.8	10.5	13.0	197
1004318A004004	4 x 4.0	0.8	12.0	14.0	266
1004318A0050005	5 x 0.5	0.6	7.2	9.4	101
1004318A00500075	5 x 0.75	0.6	7.4	9.6	123
1004318A005001	5x 1.0	0.6	8.3	10.0	142
1004318A0050015	5x 1.5	0.7	10.0	12.0	183
1004318A0050025	5 x 2.5	0.8	11.5	14.0	272