


ANYCERT-CE-H05Z1Z1-U

H05Z1Z1-U 低烟无卤绝缘护套多芯硬电缆



应用

- The halogen-free fireproof power cable has enhanced fireproof performance in case of fire. Suitable for fixed or mobile installation. As a strict safety requirement for input and connection cables, it can be installed in a dry or above room. It has the function of anti-ultraviolet and the applicable temperature range, it can be used for outdoor installation. Can not be used for direct burial.

- No toxic gas will be generated during the combustion process, comply with EN60754
- In case of fire, low smoke density complies with EN61034
- Using environmentally materials, comply with ROHS directive

结构

- Compliant with VDE0295. IEC60228 stranded fine (tinned) copper wire
- Compliant with VDE 0281.HD 21.5 & IEC 60227 low smoke halogen free LSZH insulation
- low smoke halogen free LSZH sheath (The color of insulation sheath can be customized according to customer requirements).

- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:
Mobile installation: -5 °C to + 90 °C
Fixed installation: -40 °C to + 90 °C
- Flame retardant: IEC 60332-1-2

Item	(n x mm ²)	O.D. (mm)	Item	(n x mm ²)	O.D. (mm)
1002H05Z1Z1U0020015	2x1.5	10	1002H05Z1Z1U0040015	4x1.5	11.5
1002H05Z1Z1U0020025	2x2.5	11.5	1002H05Z1Z1U0040025	4x2.5	13
1002H05Z1Z1U002004	2x4	12.5	1002H05Z1Z1U004004	4x4	14.5
1002H05Z1Z1U002006	2x6	13.5	1002H05Z1Z1U004006	4x6	16
1002H05Z1Z1U002010	2x10	16.5	1002H05Z1Z1U004010	4x10	19
1002H05Z1Z1U002025	2x25	24	1002H05Z1Z1U004025	4x25	28.5
1002H05Z1Z1U002035	2x35	27.5	1002H05Z1Z1U004035	4x35	32
1002H05Z1Z1U0030015	3x1.5	10.5	1002H05Z1Z1U0050015	5x1.5	12
1002H05Z1Z1U0030025	3x2.5	12	1002H05Z1Z1U0050025	5x2.5	14
1002H05Z1Z1U003004	3x4	13	1002H05Z1Z1U005004	5x4	16
1002H05Z1Z1U003006	3x6	14.5	1002H05Z1Z1U005006	5x6	17.5
1002H05Z1Z1U003010	3x10	17.5	1002H05Z1Z1U005010	5x10	21
1002H05Z1Z1U003025	3x25	26	1002H05Z1Z1U005025	5x25	31.5
1002H05Z1Z1U003035	3x35	29	1002H05Z1Z1U005035	5x35	35