

ANYCERT-CE/TUV-H05V-R

H05V-R single core flex PVC Wire



应用

- Installed indoors, in cable ducts and industrial equipment or underground, can be used in switches and distribution boards and also used in electrical and electronic equipment and switch gear designed for export to European countries, the equipment that need to be replaced for aviation maintenance in Europe.
- Flexible, small bending radius.
- Using environmentally materials, with ROHS directive
- Multi-standard cables CE / TUV and other approvals comply with European standards, so that the cable can adapt to different European market needs.

结构

- Compliant with VDE0295, IEC60228-2, fine stranded
- (tinned) copper wire
- Conforms to VDE 0281, HD 21.3 & IEC 60227 PVC insulation (Insulation color can be customized according to customer requirements)
- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:
Mobile installation: -5 °C to + 70 °C
Fixed installation: -40 °C to + 70 °C
- Oil resistance, flame retardant: IEC 60332.1 / HD 405.2 and VDE 0207-4

页码

Item	type	Conductor			Insulation			20 °C	70 °C	Voltage resistant
		size	wires	OD	thickness	O.D.	Max O.D.	Resistant	Resistant	
		mm ²	No./mm	mm	mm	mm	mm	Ω/km	MΩ.km	V
1002H05VR0005	stranded	0.5	7/0.30	0.90	0.6	2.12	2.6	39	0.013	2000
1002H05VR00075		0.75	7/1.37	1.1	0.6	2.33	2.8	26	0.011	
1002H05VR001		1.0	7/0.43	1.3	0.6	2.5	3.0	19.5	0.01	