

ANYAPPS-CAR CABLE-AVS AVVS

Ultra thin CAR CABLE



应用



Apply to high electric vehicles and instrument circuit

结构

Stranded bare copper
Special PVC for car only.

特点

Super slim car cable with high flexibility, high mechanical strength, heat resistance, resistance to burn, the high temperature resistant properties.

Use standard thickness, easy to cut off

Acid and alkali resistance, heat resistance, cold resistance, abrasion resistance, oil resistance, environmental protection and other characteristics

性能

Rated voltage:no standard

Rated temperature 105 ° C

Part No.	item	Conductor			Insulation		O. D.		20 °C maximum foreign resistance	70 °C minimum insulation resistance	voltage
		SIZE	Wire No. /size	O. D.	Thick ness	O. D.	nominal O. D.	maximu m O.D.			
							.				

		mm ²	No./mm	mm	mm	mm	mm	mm	Ω/Km	Ω.cm	V
200AVS0003	AVS	0.3	7/0.26	0.8	0.5	0.32	1.8	1.9	50.2	109	1000
200AVS0005		0.5	7/0.32	1	0.5	0.32	2	2.1	32.7		
200AVS0008516		0.85	16/0.26	1.2	0.5	0.32	2.2	2.3	22		
200AVS008511			11/0.32	1.2	0.5	0.32	2.2	2.3	20.8		
200AVS00125		1.25	16/0.32	1.5	0.5	0.32	2.5	2.6	14.3		
200AVS002		2	26/0.32	1.9	0.5	0.32	2.9	3.1	8.81		
200AVS003		3	41/0.32	2.4	0.6	0.4	3.6	3.8	5.59		
200AVS005		5	65/0.32	3	0.7	0.48	4.4	4.6	3.52		
200AVS0003F		0.3f	15/0.18	0.8	0.5	0.32	1.8	1.9	48.9		
200AVS0005F		0.5f	20/0.18	1	0.5	0.32	2	2.1	36.7		
200AVS00075F		0.75f	30/0.18	1.2	0.5	0.32	2.2	2.3	24.4		
200AVS000125F		1.25f	50/0.18	1.5	0.5	0.32	2.5	2.6	14.7		
200AVS002F		2.0f	37/0.26	1.9	0.5	0.32	2.9	3.1	9.5		
200AVSS0003	AVSS	0.3	7/0.26	0.8	0.3	0.24	1.4	1.5	50.2	109	1000
200AVSS0005		0.5	7/0.32	1	0.3	0.24	1.6	1.7	32.7		
200AVSS0008519		0.85	19/0.24	1.2	0.3	0.24	1.8	1.9	21.7		
200AVSS000857			7/0.40	1.1	0.3	0.24	1.8	1.9	20.8		
200AVSS00125		1.25	19/0.29	1.5	0.3	0.24	2.1	2.2	14.9		
200AVSS002		2	19/0.37	1.9	0.4	0.32	2.7	2.8	9		
200AVSS003F		0.3f	19/0.16	0.8	0.3	0.24	1.4	1.5	48.8		
200AVSS005F		0.5f	19/0.19	1	3	0.24	1.6	1.7	34.6		
200AVSS00075F		0.75f	19/0.23	1.2	0.3	0.24	1.8	1.9	23.6		
200AVSS000125F		1.25f	37/0.21	1.5	0.3	0.24	2.1	2.2	14.6		

200AVSS002F		2.0f	37/0.26	1.8	0.4	0.32	2.6	2.7	9.5		
-------------	--	------	---------	-----	-----	------	-----	-----	-----	--	--

※ Can produce cable under your special request