

ANYCERT-CE/TUV-H07V2-R

H07V2-R Single core Flex PVC Wire



应用

- Suitable for wiring or connecting wires of electrical equipment, wiring of household appliances and lighting fixtures.
- Flexible, small bending radius.
- Using environmentally materials, with ROHS directive
- Multi-standard cables CE / TUV and other approvals
- comply with European standards, so that the cable can adapt to different European market needs.

结构

- Compliant with VDE0295, IEC60228-2 stranded fine s
- (tinned) copper wire
Complies with VDE 0281.HD 21.3 & IEC 60227 PVC insulation.
- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:
Mobile installation: -5 °C to + 70 °C
Fixed installation: -40 °C to + 70 °C
- Oil resistance, flame retardant: IEC 60332.1 / HD 405.2 and VDE 0207-4

Item	mm ²	Wire mm	Thickness mm	Cable O.D. mm	Weight Kg/Km
1002H07V2R0015	1.5	0.26	0.7	2.9	21
1002H07V2R0025	2.5	0.26	0.8	3.5	33
1002H07V2R004	4	0.31	0.8	4.0	47
1002H07V2R006	6	0.31	0.8	4.6	66
1002H07V2R010	10	0.41	1.0	6.0	111
1002H07V2R016	16	0.41	1.0	7.0	165
1002H07V2R025	25	0.41	1.2	8.7	254
1002H07V2R035	35	0.41	1.2	9.7	343
1002H07V2R050	50	0.41	1.4	12.2	494
1002H07V2R070	70	0.51	1.4	14.0	678
1002H07V2R095	95	0.51	1.6	15.2	895
1002H07V2R120	120	0.51	1.6	17.2	1149
1002H07V2R150	150	0.51	1.8	18.9	1416
1002H07V2R185	185	0.51	2.0	21.0	1724
1002H07V2R240	240	0.51	2.2	25.2	2285

*customized cable acceptable