

ANYCERT-UL/CUL/CSA-UL 2990

UL 2990low voltage computer cable



应用

- Suitable for monitors, computers or e-commerce equipment.

- Rated temperature: 80 °C
- Working voltage: 30V
- Oil resistance, flame retardant:
CSA FT1 and UL VW-1

结构

- Stranded strands of fine bare copper wire
- conductors
- PVC or SRPVC mixed core wire insulation (color can be customized according to customer requirements)

Stranded composite cable

- * Insulated plastic film coating
- * Aluminum foil Mylar 100% coated shield
- * (Tinned) copper wire shield braided or wound, coverage rate up to 85%
- PVC mixture outer sheath (color can be customized according to customer requirements)
- * mark for optional structure.

Item	Conductor			Insulation		Drain wire	shield	Jacket		Max. Conduct or resist.	Min. insulation resistance	Voltage resistant
	AWG	No	No. /mm	Thick mm	O. D. mm	No. /mm		Thick mm	O. D. mm	Ω@20°C	MΩ.Km	V
1001101530A	30	12	7/0.10	0.23	0.84	7/0.16	24x5/0.12	0.76	6.50	354	10	500
1001101530B		21	7/0.10	0.12	0.62	-	24x5/0.10	0.76	6.0			
1001101528A	28	19p	7/0.127	0.24	0.85	7/0.16	24x9/0.12	0.76	10.2	223		
1001101528B		25p	7/0.127	0.12	0.61	7/0.16	24x8/0.12	0.76	8.45			

* Can provide customers with special order

If you have special requirements for core wire, outer sheath, operating temperature range, etc., please consult