

ANYCERT-UL/CUL/CSA-UL 20276

UL 20276 聚氯乙烯绝缘护套控制电缆



应用

- It is suitable for internal wiring and inter-instrument connection of electrical equipment such as computers, electronics, and peripheral equipment.

- Rated temperature: 80 °C
- Working voltage: 30V
- Oil resistance, flame retardant:
- CSA FT1 and UL VW-1

结构

- Strands of fine stranded strands of bare copper or tinned wire
- PVC or SRPVC mixed core wire insulation (color can be customized according to customer requirements)
- Stranded composite cable
 - Insulated plastic film coating
- Aluminum foil Mylar 100% coated shield
 - Copper wire (tinned) shield braided or wound, coverage rate up to 85%
- PVC mixture outer sheath (color can be customized according to customer requirements)
- * mark for optional structure

Item	type	conductor		core	insulation		AL foil	Drain wire	braid	Jacket	
		size	wire		thick	O.D.				thick	O.D.
		AWG	No./mm	pcs	mm	mm	mmxmm	No./No.mm	mm	mm	mm
100120276003028	stranded	28	7/0.127	3	0.23	0.88	0.03x8	7/0.127	16/4/0.12	0.51	3.6
100120276004028		28	7/0.127	4	0.23	0.88	0.03x10	7/0.127	16/4/0.12	0.51	3.82
100120276005028		28	7/0.127	5	0.23	0.88	0.03x10	7/0.127	16/4/0.12	0.51	4.08
100120276006028		28	7/0.127	6	0.23	0.88	0.03x12	7/0.127	16/5/0.12	0.51	4.34
100120276007028		28	7/0.127	7	0.23	0.88	0.03x12	7/0.127	16/5/0.12	0.51	4.34
100120276008028		28	7/0.127	8	0.23	0.88	0.03x12	7/0.127	16/5/0.12	0.51	4.6
100120276009028		28	7/0.127	9	0.23	0.88	0.03x16	7/0.127	16/6/0.12	0.51	4.96
100120276010028		28	7/0.127	10	0.23	0.88	0.03x16	7/0.127	16/6/0.12	0.51	5.22
100120276011028		28	7/0.127	11	0.23	0.88	0.03x16	7/0.127	16/6/0.12	0.51	5.36
100120276012028		28	7/0.127	12	0.23	0.88	0.03x16	7/0.127	16/6/0.12	0.51	5.36
100120276013028		28	7/0.127	13	0.23	0.88	0.03x16	7/0.127	16/7/0.12	0.51	5.58
100120276014028		28	7/0.127	14	0.23	0.88	0.03x16	7/0.127	16/7/0.12	0.51	5.58
100120276015028		28	7/0.127	15	0.23	0.88	0.03x18	7/0.127	16/8/0.12	0.51	5.84
100120276002026		26	7/0.16	2	0.23	0.98	0.03x8	7/0.16	16/4/0.12	0.51	3.66
100120276003026		26	7/0.16	3	0.23	0.98	0.03x10	7/0.16	16/4/0.12	0.51	3.81
100120276004026		26	7/0.16	4	0.23	0.98	0.03x10	7/0.16	16/4/0.12	0.51	4.07

Max.Conductor resistant:223.75Ω/km

Min. insulation resistance:5.0MΩ.km

Voltage resistant:500V