

# ANYCERT-CE-H03V2V2H2-F/H05V2V2H2-F

## Fire resistant PVC/PVC Flat Cable



### 应用

- Suitable for daily applications such as home environment, kitchen, office, etc., and can also be used in humid conditions.
- High temperature resistance 90 °C , moisture proof, flame retardant.
- Meet the most stringent electrical and mechanical performance requirements.
- Using environmentally protect materials, in line with ROHS directive.  
Complies with European CE standards.

### 结构

- Compliant with VDE0295. IEC60228 fine stranded (tinned) copper wire
- Meet VDE 0281.HD 21.5 & IEC 60227 special flame retardant PVC insulation, PVC jacket.
- Working voltage: H03V2V2-F: 300V/300V  
H05V2V2-F: 300V/500V
- Minimum bending radius:
- Mobile installation: 15x cable outer diameter  
Fixed installation: 4x cable outer diameter
- Operating temperature range:  
Mobile installation: -5 °C to +90 °C  
Fixed installation: -40 °C to +90 °C

页码

Item	Section size mm <sup>2</sup>	Cable O.D.mm	Weight Kg/km
1002H03V2V2H2F0020005	2x0.5	3.2*5.4	33
1002H03V2V2H2F00200075	2x0.75	4*4.6	41
1002H05V2V2H2F0020001	2*1	4.2*6.8	48
1002H05V2V2H2F0020015	2*1.5	4.6*7.6	59
1002H05V2V2H2F0020025	2*2.5	5.7*9.4	82
1002H05V2V2H2F002004	2*4	5.9*9.7	114
1002H05V2V2H2F002006	2*6	6.5*10.9	155
1002H05V2V2H2F002010	2*10	8.4*14.5	257
1002H03V2V2H2F0030005	3x0.5	3.6*7.6	45.2
1002H03V2V2H2F00300075	3x0.75	3.9*8.3	56.8
1002H03V2V2H2F0030001	3*1	4.1*8.7	67.8
1002H05V2V2H2F0030015	3*1.5	4.6*10.2	84.3
1002H05V2V2H2F0030025	3*2.5	5.3*11.9	119
1002H05V2V2H2F003004	3*4	6*13.7	167
1002H05V2V2H2F003006	3*6	6.5*15.3	223
1002H05V2V2H2F003010	3*10	8.4*20	369