

ANYCERT-SAA-SEC

Australian standard multi-core security alarm wire



应用

- Suitable for export to Australia, subject to Australian Standard alert lines.

结构

- Stranded conductors or single copper wire conductors
- conforming to AS1125
- Special PVC V-75 core wire insulation according to AS3808
5V-75 PVC sheath, generally white, brown or gray to AS3808
(All colors can be customized upon request)

特点

- Use standard thickness, easy to peel, easy to cut
 - oil resistance, moisture resistance, mold resistance,
 - environmental protection and other characteristics
- SAA certification for cable use in Australia, New Zealand

性能

- Operating voltage: Extremely low voltage, not suitable for
 - connection to mains power.
- Operating temperature range: 75°C

Item	size	conductor	Insulation thickness	Jacket Thickness	Cable O.D.	Weight KG/100M
1003security00300022	3x0.22	7/0.20	0.30	0.5	3.6	1.7
1003security00400022	4x0.22	7/0.20	0.30	0.6	3.9	2.2
1003security00600022	6x0.22	7/0.20	0.30	0.6	4.6	3.4
1003security00700022	7x0.22	7/0.20	0.30	0.6	4.85	3.7
1003security00800022	8x0.22	7/0.20	0.30	0.6	5.3	4.2
1003security01200022	12x0.22	7/0.20	0.30	0.6	6.4	6.1
1003security01800022	18x0.22	7/0.20	0.30	0.6	7.4	9.2
1003security02500022	25x0.22	7/0.20	0.30	0.6	8.5	12
1003security00300044	3x0.44	14/0.20	0.32	0.5	4.25	2.7
1003security00400044	4x0.44	14/0.20	0.32	0.5	4.6	3.3
1003security00600044	6x0.44	14/0.20	0.32	0.5	5.5	5.2
1003security00800044	8x0.44	14/0.20	0.32	0.5	6.7	6.8

*customized cable acceptable