

ANYCERT-UL/CUL/CSA-UL 20379

UL 20379 Multi core shield control cable



应用

- Suitable for monitors, computers or e-commerce equipment.

- Rated temperature: 80 °C
- Working voltage: 30V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

结构

- Strands of fine stranded strands of bare copper
- wire above 30AWG
- PVC mixed core wire insulation (color can be customized according to customer requirements)
- Stranded composite cable
- 100% coverage of special aluminum foil Mylar tape
 - * Copper wire (tinned) shield braided or wound, coverage rate up to 85%
 - PVC mixture outer sheath (color can be customized according to customer requirements)
 - * mark for optional structure

Item	conductor			Insulation		shield		Jacket		20°C Resistant
	size	wire	O.D.	thick	O.D.	AL	braid	thick	O.D	
	AWG	No./mm	mm	mm	mm	foil		mm	mm	Ω/km
100120379004030	30	4	7/0.10	0.20	0.70	Y	16x4/0.10	0.38	3.0	354
100120379010030		10	7/0.10	0.13	0.56	Y	70/0.10	0.50	3.40	
100120379018030		18	7/0.10	0.14	0.58	-	24x8/0.10	0.60	4.80	
100120379024030		24	7/0.10	0.13	0.56	Y	16x8/0.10	0.44	4.50	
10012037928006028	28	6	7/0.127	0.15	0.68	Y	53/0.12	0.50	3.40	223
10012037928008028		8	7/0.127	0.12	0.63	Y	16x3/0.10	0.55	3.70	
10012037928018028		18	7/0.127	0.10	0.58	Y	24x8/0.10	0.70	5.0	
10012037928025028		25	7/0.127	0.12	0.62	Y	16x10/0.10	0.50	5.20	

Can provide customers with special order

If you have special requirements for core wire, outer sheath, operating temperature range, etc., please consult.