

ANYCERT-SAA-AS/NZS 3191-250/440V

Multi core Flexible Power Cable



应用

- Used for power, control and signal transmission lines for electrical, instrumentation and electronic equipment and automation devices. Also used in domestic, commercial and industrial direct buried or underground pipelines, without damage to conductors and PVC. Particularly suitable for export to Australia for internal installation in mobile homes, containers, refrigerated cabinets and caravans.

结构

- Conductor according to AS/NZS1125, copper wire
 - class 5
 - Insulated to AS/NZS 3808, PVC V90
- Conforms to AS/NZS 3808 standard sheath, PVC 5V-90

Operating voltage: 250/440V

Flame retardant and flame retardant: IEC 60332.1

特点

- Environmentally friendly materials, no harmful substances, in compliance with RoHS or REACH directives
- SAA-compliant cable for use in Australia, New Zealand
- Soft and easy to install.

性能

- Minimum bending radius:
- Mobile installation: 15x cable OD
- Fixed installation: 4x cable OD
- Operating temperature range:
- Mobile installation: -5° C to +90° C
- Fixed installation: -40° C to +90° C

Type	Core*size	O.D.	Weight
3191R	2×0.75	6.6	42.7
3191R	3×0.75	7.0	55.1
3191R	4×0.75	7.6	68.4
3191R	5×0.75	8.4	85.5
3191R	2×1.0	7.0	49.6
3191R	3×1.0	7.4	64.9
3191R	4×1.0	8.2	84.7
3191R	5×1.0	9.0	101.4
3191R	2×1.5	8.0	66.2
3191R	3×1.5	8.7	92.0
3191R	4×1.5	9.6	119.7

Type	Core*size	O.D.	Weight
3191R	5×1.5	10.7	148.6
3191R	2×2.5	9.6	102.0
3191R	3×2.5	10.4	141.0
3191R	4×2.5	11.3	177.7
3191R	5×2.5	12.5	220.2
3191R	2×4.0	10.8	138.2
3191R	3×4.0	11.6	193.7
3191R	4×4.0	12.7	246.5
3191R	5×4.0	14.3	312.3

*customized cable acceptable.