


ANYCERT-CE/TUV-H05Z1Z1-F

H05Z1Z1-F LSZH Multi Core Cable



应用

- The halogen-free fireproof power cable has enhanced fireproof performance in case of fire. Suitable for fixed or mobile installation. As a strict safety requirement for input and connection cables, it can be installed in a dry or above room. It has the function of anti-ultraviolet and the applicable temperature range, it can be used for outdoor installation. Can not be used for direct burial..
- No toxic gas will be generated during the combustion process, comply with EN60754
- In case of fire, low smoke density complies with EN61034
- Using environmentally materials, comply with ROHS directive
- Multi-standard cables CE / TUV and other approvals comply with European standards.

结构

- Compliant with VDE0295. IEC60228 stranded fine (tinned) copper wire
- Compliant with VDE 0281.HD 21.5 & IEC 60227 low smoke halogen free LSZH insulation
- low smoke halogen free LSZH sheath (The color of insulation sheath can be customized according to customer requirements).
- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:
- Mobile installation: -5 °C to + 90 °C
- Fixed installation: -40 °C to + 90 °C
- Flame retardant: IEC 60332-1-2

Item	(n x mm ²)	O.D. (mm)	Item	(n x mm ²)	O.D. (mm)
005LSZH05Z1Z1002075	2x0.75	7.6	005LSZH05Z1Z1004075	4x0.75	8.6
005LSZH05Z1Z100201	2x1	8.0	005LSZH05Z1Z100401	4x1	9.4
005LSZH05Z1Z1002015	2x1.5	9.0	005LSZH05Z1Z1004015	4x1.5	11.0
005LSZH05Z1Z1002025	2x2.5	11.0	005LSZH05Z1Z1004025	4x2.5	13.0
005LSZH05Z1Z100204	2x4	12.4	005LSZH05Z1Z100404	4x4	14.4
005LSZH05Z1Z1003075	3x0.75	8.0	005LSZH05Z1Z1004075	5x0.75	17.1
005LSZH05Z1Z100301	3x1	8.4	005LSZH05Z1Z100501	5x1	10.0
005LSZH05Z1Z1003015	3x1.5	9.8	005LSZH05Z1Z1005015	5x1.5	12.0
005LSZH05Z1Z1003025	3x2.5	12.0	005LSZH05Z1Z1005025	5x2.5	14.0
005LSZH05Z1Z100304	3x4	13.2	005LSZH05Z1Z100504	5x4	15.6