

ANYCERT-CE-H03VVH2-F/H05VVH2-F

PVC/PVC Flat Cable



应用

- Suitable for power connection of general electronic and electrical equipment.
- Small outer diameter to save space for cable installation
- Meet strict electrical and mechanical performance requirements
- Using environmentally protect materials, in line with ROHS directive
Complies with European CE standards.

结构

- Compliant with VDE0295. IEC60228 fine stranded (tinned) copper wire
- Meet VDE 0281.HD 21.5 & IEC 60227 special flame retardant PVC insulation, PVC jacket.
- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:
Mobile installation: -5 °C to + 70 °C
Fixed installation: -40 °C to + 70 °C
- Oil resistance, flame retardant: IEC 60332-1-2

Item	Section size mm ²	Cable O.D.mm	Weight Kg/km
1002H03V2V2H2F0020005	2x0.5	3.2*5.4	33
1002H03V2V2H2F00200075	2x0.75	4*4.6	41
1002H05V2V2H2F002001	2*1	4.2*6.8	48
1002H03V2V2H2F0030005	3x0.5	3.6*7.6	45.2
1002H03V2V2H2F00300075	3x0.75	3.9*8.3	56.8
1002H03V2V2H2F003001	3*1	4.1*8.7	67.8
1002H05V2V2H2F0020015	2*1.5	4.6*7.6	59
1002H05V2V2H2F0020025	2*2.5	5.7*9.4	82
1002H05V2V2H2F002004	2*4	5.9*9.7	114
1002H05V2V2H2F002006	2*6	6.5*10.9	155
1002H05V2V2H2F002010	2*10	8.4*14.5	257
1002H05V2V2H2F0030015	3*1.5	4.6*10.2	84.3
1002H05V2V2H2F0030025	3*2.5	5.3*11.9	119
1002H05V2V2H2F003004	3*4	6*13.7	167
1002H05V2V2H2F003006	3*6	6.5*15.3	223
1002H05V2V2H2F003010	3*10	8.4*20	369

*customized cable acceptable