

# ANYCERT-CE-H03V2V2-F/H05V2V2-F

## Fire resistant PVC/PVC Cable



### 应用

- Suitable for daily applications such as home environment, kitchen, office, etc., and can also be used in humid conditions.

- High temperature resistance 90 °C, moisture proof, flame retardant.
- Meet the most stringent electrical and mechanical performance requirements.

Using environmentally protect materials, in line with ROHS directive.

Complies with European CE standards.

### 结构

- Compliant with VDE0295. IEC60228 fine stranded (tinned) copper wire
- Meet VDE 0281.HD 21.5 & IEC 60227 special flame retardant PVC insulation, PVC jacket.

- Working voltage: H03V2V2-F: 300V/300V
- H05V2V2-F: 300V/500V

Minimum bending radius:

Mobile installation: 15x cable outer diameter

- Fixed installation: 4x cable outer diameter

Operating temperature range:

Mobile installation: -5 °C to +90 °C

- Fixed installation: -40 °C to +90 °C

- Flame retardant: IEC 60332-1-2

Item	( nxmm2 )	thickness ( mm )	Cable OD ( mm )		Weight Km ( kg )
			max	min	
1002H03V2V2F0020005	2x0.5	0.6	5.2	6.8	39
1002H03V2V2F00200075	2x0.75	0.6	5.6	7.2	48
1002H03V2V2F0030005	3x0.5	0.6	5.6	7.2	48
1002H03V2V2F00300075	3x0.75	0.6	6.0	7.6	59
1002H05V2V2F0020005	2x0.5	0.6	5.6	7.2	53
1002H05V2V2F00200075	2x0.75	0.6	6.0	7.6	63
1002H05V2V2F002001	2x1.0	0.6	6.4	8.0	71
1002H05V2V2F0020015	2x1.5	0.7	7.4	9.0	90
1002H05V2V2F0020025	2x2.5	0.8	8.9	11.0	132
1002H05V2V2F002004	2x4.0	0.8	10.0	12.0	177
1002H05V2V2F0030005	3x0.5	0.6	5.9	7.7	56
1002H05V2V2F00300075	3x0.75	0.6	6.4	8.0	67
1002H05V2V2F003001	3x1.0	0.6	6.8	8.4	77
1002H05V2V2F0030015	3x1.5	0.7	8.0	9.8	122
1002H05V2V2F0030025	3x2.5	0.8	9.6	12.0	180