

# ANYCERT-UL/CUL/CSA-UL 2569

## UL 2569 PVC Parallel Cable



### 应用

- It is suitable for the internal connecting wires of general electronic equipment and electrical

### 结构

- The conductor uses single or stranded wire
- 30-10AWG bare copper or tinned wire.  
PVC mixed core wire insulation (color can be customized according to customer requirements)
- Rated temperature: 80 °C
- Working voltage: 30V
- Oil resistance, flame retardant:

页码

| Item           | conductor |     |         |      | Insulation |      |       | Resistance<br>At20°C |
|----------------|-----------|-----|---------|------|------------|------|-------|----------------------|
|                | AWG       | pcs | Wire mm | O.D. | Thickness  | O.D. | cores |                      |
| 10012569002030 | 30        | 7   | 0.100   | 0.30 | 0.76       | 1.82 | 2     | 354.00               |
| 10012569002028 | 28        | 7   | 0.127   | 0.38 | 0.76       | 1.90 | 2     | 223.00               |
| 10012569002026 | 26        | 7   | 0.160   | 0.48 | 0.76       | 2.00 | 2     | 139.00               |
| 10012569002024 | 24        | 11  | 0.160   | 0.61 | 0.76       | 2.13 | 2     | 88.90                |
| 10012569002022 | 22        | 17  | 0.160   | 0.76 | 0.76       | 2.28 | 2     | 51.35                |
| 10012569002020 | 20        | 21  | 0.180   | 0.95 | 0.76       | 2.47 | 2     | 32.85                |
| 10012569002018 | 18        | 41  | 0.160   | 1.18 | 0.76       | 2.70 | 2     | 23.30                |
| 10012569002016 | 16        | 26  | 0.254   | 1.49 | 0.76       | 3.01 | 2     | 13.32                |
| 10012569003030 | 30        | 7   | 0.100   | 0.30 | 0.76       | 1.82 | 3     | 354.00               |
| 10012569003028 | 28        | 7   | 0.127   | 0.38 | 0.76       | 1.90 | 3     | 223.00               |
| 10012569003026 | 26        | 7   | 0.160   | 0.48 | 0.76       | 2.00 | 3     | 139.00               |
| 10012569003024 | 24        | 11  | 0.160   | 0.61 | 0.76       | 2.13 | 3     | 88.90                |
| 10012569003022 | 22        | 17  | 0.160   | 0.76 | 0.76       | 2.28 | 3     | 51.35                |
| 10012569003020 | 20        | 21  | 0.180   | 0.95 | 0.76       | 2.47 | 3     | 32.85                |
| 10012569003018 | 18        | 41  | 0.160   | 1.18 | 0.76       | 2.70 | 3     | 23.30                |
| 10012569003016 | 16        | 26  | 0.254   | 1.49 | 0.76       | 3.01 | 3     | 13.32                |
| 10012569004030 | 30        | 7   | 0.100   | 0.30 | 0.76       | 1.82 | 4     | 354.00               |
| 10012569004028 | 28        | 7   | 0.127   | 0.38 | 0.76       | 1.90 | 4     | 223.00               |
| 10012569004026 | 26        | 7   | 0.160   | 0.48 | 0.76       | 2.00 | 4     | 139.00               |
| 10012569004024 | 24        | 11  | 0.160   | 0.61 | 0.76       | 2.13 | 4     | 88.90                |
| 10012569004022 | 22        | 17  | 0.160   | 0.76 | 0.76       | 2.28 | 4     | 51.35                |
| 10012569004020 | 20        | 21  | 0.180   | 0.95 | 0.76       | 2.47 | 4     | 32.85                |
| 10012569004018 | 18        | 41  | 0.160   | 1.18 | 0.76       | 2.70 | 4     | 23.30                |