

ANYCERT-CE/TUV-H05V2-R

H05V2-R 单芯绞合导体聚氯乙烯绝缘软电线



应用

- Installed indoors, in cable ducts and industrial equipment or underground, can be used in switches and distribution boards and also used in electrical and electronic equipment and switch gear designed for export to European countries, the equipment that need to be replaced for aviation maintenance in Europe.
- Flexible, small bending radius.
- Using environmentally materials, with ROHS directive
- Multi-standard cables CE / TUV and other approvals comply with European standards, so that the cable can adapt to different European market needs.

结构

- Compliant with VDE0295, IEC60228-2 stranded fine s
- (tinned) copper wire
Complies with VDE 0281, HD 21.3 & IEC 60227 PVC insulation.
- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:
Mobile installation: -5 °C to + 70 °C
Fixed installation: -40 °C to + 70 °C
- Oil resistance, flame retardant: IEC 60332.1 / HD 405.2 and VDE 0207-4

Item	mm ²	Wire/pcs	Wire OD mm	Max.resistant 20°C Ohm/km	Insulation thickness mm	Cable O.D. mm	Weight Kg/km
1002H05V2R0005	0.5	7	0.9	36.0	0.6	2.2	9
1002H05V2R00075	0.75	7	1.1	24.5	0.6	2.4	12
1002H05V2R001	1.0	7	1.3	18.1	0.6	2.6	15

*customized cable acceptable

