

ANYCERT-UL/CUL-UL 21143

UL 21143LSZH Multi core cable (shield optional)



应用

- It is suitable for the installation and fixed laying of free non-continuous reciprocating movement without stress relief or forced guidance, such as machine tool manufacturing, complete equipment installation engineering, painting workshop, power station, freezing equipment, office automation equipment, etc.
- Working voltage: 300V or 600V
- Rated temperature: 80 °C
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

结构

- Strands of fine stranded strands of bare copper wire or tinned copper wire
- Special FRPE low-smoke halogen-free mixed core wire insulation (color can be customized according to customer requirements)
- Stranded composite cable
 - * Insulated plastic film coating or special FRPE mixture inner sheath
 - * Copper wire (tinned) shield braid, coverage rate up to 85%
 - Special FRPE low-smoke halogen-free mixture outer sheath (color can be customized according to customer requirements)
 - * mark for optional structure

Item	conductor			insulation			Shield		Jacket		resistant
	AWG	pcs	OD	core	thick	OD	AL	braiding	thick	OD	
100121143002030	30	7/0.10	0.30	2	0.25	0.80	AL	16/4/0.10	0.76	3.52	319.26
100121143003030	30	7/0.10	0.30	3	0.25	0.80	AL	16/4/0.10	0.76	3.64	319.26
100121143004030	30	7/0.10	0.30	4	0.25	0.80	AL	16/4/0.10	0.76	3.85	319.26
100121143005030	30	7/0.10	0.30	5	0.25	0.80	AL	16/4/0.10	0.76	5.42	319.26
100121143002028	28	7/0.127	0.38	2	0.25	0.80	AL	16/4/0.10	0.76	3.68	197.94
100121143003028	28	7/0.127	0.38	3	0.25	0.80	AL	16/4/0.10	0.76	3.82	197.94
100121143004028	28	7/0.127	0.38	4	0.25	0.80	AL	16/4/0.10	0.76	4.05	197.94
100121143005028	28	7/0.127	0.38	5	0.25	0.80	AL	16/4/0.10	0.76	4.30	197.94
100121143002026	26	7/0.16	0.48	2	0.25	0.95	AL	16/4/0.10	0.76	3.82	124.71
100121143003026	26	7/0.16	0.48	3	0.25	0.95	AL	16/4/0.10	0.76	3.97	124.71
100121143004026	26	7/0.16	0.48	4	0.25	0.95	AL	16/4/0.10	0.76	4.21	124.71
100121143005026	26	7/0.16	0.48	5	0.25	0.95	AL	16/4/0.10	0.76	4.49	124.71
100121143002024	24	11/0.16	0.61	2	0.25	1.10	AL	16/5/0.10	0.76	4.12	98.54
100121143003024	24	11/0.16	0.61	3	0.25	1.10	AL	16/5/0.10	0.76	4.29	98.54
100121143004024	24	11/0.16	0.61	4	0.25	1.10	AL	16/5/0.10	0.76	4.58	98.54
100121143005024	24	11/0.16	0.61	5	0.25	1.10	AL	16/5/0.10	0.76	4.89	98.54
100121143002022	22	17/0.16	0.76	2	0.25	1.26	AL	16/5/0.10	0.76	4.45	51.35
100121143003022	22	17/0.16	0.76	3	0.25	1.26	AL	16/5/0.10	0.76	4.63	51.35
100121143004022	22	17/0.16	0.76	4	0.25	1.26	AL	16/5/0.10	0.76	4.96	51.35
100121143005022	22	17/0.16	0.76	5	0.25	1.26	AL	16/5/0.10	0.76	5.32	51.35

*可为客户提供特殊定做