

ANYAPPS-CAR CABLE-AV CABLE

Low voltage AV CAR CABLE



应用



Apply to high electric vehicles and instrument circuit

结构

Stranded bare copper

Special XL-PVC for car only.

特点

High mechanical strength, heat 105 °C, high temperature resistant properties.

Pass the JIS C 3406-93 burning resistance test

Use standard thickness, easy to cut off

Acid and alkali resistance, heat resistance, cold resistance, abrasion resistance, oil resistance, environmental protection and other characteristics

性能

Rated voltage: no standard

Rated temperature 105 °C

Part No.	Conductor		Insulation				Maximum conduct or resistanc e at 20℃ Ω.mm	voltage V
	SIZE	Wire No. /size	O. D.	Thick ness		O. D.		
	mm2	No./mm	mm	mm	mm	mm		
200AV0005F	0.5f	20/0.18	1		2.2	2.4	36.7	
200AV0005	0.5	7/0.32	1		2.2	2.4	32.7	
200AV00075F	0.75f	30/0.18	1.2		2.4	2.6	24.4	
200AV00085	0.85	11/0.32	1.2	0.6	2.4	2.6	20.8	
200AV00125F	1.25f	50/0.18	1.5		2.7	2.9	14.7	
200AV00125	1.25	16/0.32	1.5		2.7	2.9	14.3	1000
200AV002	2	26/0.32	1.9		3.1	3.4	8.81	
200AV003	3	41/0.32	2.4	0.7	3.8	4.1	5.59	
200AV005	5	65/0.32	3	0.8	4.6	4.9	3.52	
200AV008	8	50/0.45	3.7	0.9	5.5	5.8	2.32	
200AV015	15	84/0.45	48		7	7.4	1.38	
200AV020	20	41/0.80	6	1.1	8.2	8.8	0.887	

※ Can produce cable under your special request