

ANYAPPS-SECURITY CABLE-COAX CABLE WITH POWER CORD

Coax cable with power cord used to
Video Monitoring System



应用



The standard network system cable. This cable is the first choice for Network project and CATV project .

结构

RG59
Conductor: Single or strands of fine (tin) copper wire,ccs etc.
Insulation :PE Foamed or PE Solid
AL foil tape 100% covered
(optional single non-stick aluminum foil, single stick aluminum foil, double sticky aluminum foil, non-stick double-sided aluminum foil and so on)
Copper or tinned copper wire braid or spiral shielding. The coverage of 85%
(optional Al-mg,CCA and so on)
Sheath:PVC mixture(color can be customized according to customer requirements)
power cord
strands of fine (tin) copper wire
Sheath:PVC mixture(usually black with white color)

特点

Meet UL444 standards, UL13 standards, UL1685 fire test, NEC 800, NEC725
Without noxious material,acc. To ROHS.

Stable performance, signal transmission good, stable quality, the picture without snow
 This product conforms EEC procedures 73/23 (low voltage procedures) of CE rules
 The CE authentication, make cable can use in Europe and other north American market at the same time.

性能

Rated voltage:300V

operating temperature:Mobile installation:-5 ° C to + 80 ° C, fixed installation:-40 ° C to 80 ° C

Part No.	conductor		Insulation O.D.	Insulation material	shielding		OD mm	Sheath material	impedance ohm	capacitance pF/m	attenuation dB/km
	No./mm	材料			mm	Wrapped with aluminum foil					
SECURG59P00205	1/0.643	CU/CCS	3.66	PEF	100%	96/112/128/0.12 BC/AL/TC	6.1	PVC	75	41	66
	24/0.15	CU	2.3	PVC	/	/	2.3*4.6	/			

※ Can produce cable under your special request