

ANYAPPS- CONTAINER HOUSE-COAX

CABLE

集装箱房活动房专用电视线

Coax Cable used to

Locomotive house & Container house



应用



Suit for audio / video, radio, cable TV signal transmission

结构

Single or strand(Tin) copper wires, or CCA or CCS as conductor, PEF or PE core insulation.

Al Foil 100% coverage (Optional: non-self-adhesive single-sided aluminum foil, single-sided self-adhesive aluminum foil, double-sided self-adhesive aluminum foil, double-sided non-self-adhesive aluminum foil)

Special PVC jacket (Colors can be determined by customers)

特点

Comply with UL444,UL13,UL1685 fire resistant test, NEC.800.NEC725

Environmental and ROHS

SAA / UL / CSA / CE / BS standard, so the cable can be used in Australia, America, Europe and other markets.

性能

Rated voltage: 300V,
 Temperature Range: Movable installation: -5° C to +80 ° C
 Fixed installation: -40 ° C to +80° C
 Impedance: 75 ± 3Ω
 Rated temperature: 70 ° C
 Rated capacitance: 54 ± 3 pF / m
 Transfer speed: 85%
 Return Loss (100 meters): 20db
 Attenuation: 69Db/km

Item	Style	Conductor		Insulation O.D. mm	Braid No./mm	Cable O.D. mm	Jacket material
		No./mm	Material				
200BuildingRG	RG-6/U	1/1.02	CU/CCS	4.7	32/48/64/80/96/112/0.12CU/AL/TC	7.0	PVC

※ Can produce cable under your special request