

# ANYCERT-CE/TUV-H05V2-K

## H05V2-K



### 应用

This type of flexible cable is suitable for internal connection of equipment and can also be used to connect lighting equipment. It can be used in model systems and can be laid in open or embedded bushings. This product has obtained the certification required by the European market. Electrical Equipment.

- Flexible, small bending radius.
- Using environmentally materials, with ROHS directive
- Multi-standard cables CE / TUV and other approvals
- comply with European standards, so that the cable can adapt to different European market needs.

### 结构

Compliant with VDE0295, IEC60228-2 stranded fine s (tinned) copper wire  
Complies with VDE 0281, HD 21.3 & IEC 60227 PVC insulation

- Working voltage: 300 / 500V
- Minimum bending radius: 12x cable outer diameter
- Operating temperature range:  
Mobile installation: -5 °C to + 70 °C  
Fixed installation: -40 °C to + 70 °C
- Oil resistance, flame retardant: IEC 60332.1 / HD 405.2 and VDE 0207-4

Item	type	conductor			Insulation			20 °C Resistant	70°C Resistant	Voltage resistant
		section	wires	OD	thickness	O.D.	Max O.D.			
		mm <sup>2</sup>	No./mm	mm	mm	mm	mm	Ω/km	MΩ.km	V
1002H05V2K0005	stranded	0.5	16/0.20	0.92	0.6	2.12	2.6	39	0.013	2000
1002H05V2K00075		0.75	24/0.20	1.13	0.6	2.33	2.8	26	0.011	
1002H05V2K001		1.0	32/0.20	1.3	0.6	2.5	3	19.5	0.01	

\*customized cable acceptable