

# ANYCERT-CE-H05VVH6-F/H07VVH6-F

## PVC Flat Power Cable



### 应用

- This PVC insulated flat flexible sheathed cable can be used as power and control cables, installed on cable tracks, conveyors, can be used in buildings, transportation systems, cranes, elevators, etc., suitable for severe bending and reciprocating movement, can withstand medium stress.
- Reduced size means more space savings than round cables
- Has a smaller bending radius than round cables
- The horizontal discharge of the core wire will not cause the phenomenon that the cables are twisted together

### 结构

- Compliant with VDE0295. IEC60228 fine stranded (tinned) copper wire
- Meets VDE 0281.HD 21.5 & IEC 60227 polyvinyl chloride PVC insulation
- Cores arranged in parallel
- Complies with VDE 0281.HD 21.5 & IEC 60227 polyvinyl chloride PVC sheath
- Working voltage: 450 / 750V
- Minimum bending radius:  
Mobile installation: 1.5x cable outer diameter  
Fixed installation: 4x cable outer diameter
- Operating temperature range:  
Mobile installation: -5 °C to + 70 °C  
Fixed installation: -40 °C to + 70 °C
- Flame retardant: IEC 60332-1-2

页码

Item	Cores*section size mm <sup>2</sup>	Cable O.D. mm	Weight Kg/km
1002H07VVH6F00400075	4x0.75	4.2x12.6	100
1002H07VVH6F0040001	4x1	4.4x13.4	108
1002H07VVH6F0040015	4x1.5	5.2x14.5	135
1002H07VVH6F004025	4x2.5	5.9x17.5	193
1002H07VVH6F00404	4x4	6.9x20.0	273
1002H07VVH6F00406	4x6	7.4x22.0	360
1002H07VVH6F004010	4x10	9.3x27.6	584
1002H05VVH6F01200075	12x0.75	34.5x4.8	293
1002H05VVH6F02000075	20x0.75	56.5x4.6	505
1002H05VVH6F0200001	20x1.0	61.0x4.8	586
1002H05VVH6F02400075	24x0.75	61.5x5.2	567

\*customized cable acceptable